

TREVAYE TFGHF 180c CAMPER SPEC SHEET

Body – gel coated finished reinforced fibreglass (polar white)

Chassis – 50 x 25 x 2mm SHS 30 x 30 x 3mm angle duragal zinc coated, powder coated.

Safety chains – compliant 8mm x 2

Tow Hitch – Trevaye compliant (750kg) inc swivel and 50mm coupling

Suspension – double leaf spring, shackle, slipper

Axle – square drop axle 750kg rated stubs and tapered sealed bearings.

Wheels – 13 “ x 5.5” alloy safety rims, tubeless .5 stud

Tyres – 165/65R13 77H tubeless

Braking system – Trevaye hydraulic override disc

Wiring – STD 7 pin automotive flat wiring plug

Lighting – compliant LED lighting

Top bows – steel or aluminium sliding

Top – Australian billabong cotton canvas 8oz.

Bed – STD double bed, 50mm high density foam mattress

Bed base – tubular steel sliding & ply hinged with 2 gas struts

Luggage area – 1500mm x 900mm x 400mm, carpet. Approx .54 cub mtr

Hard floor area – vinyl covering

Jockey wheel – STD light swivel vertical sliding or HD swing 6” wheel winding

Rear Stand – vertical sliding

Open hard floor area – 1650mm x 1200mm standing room height area minimum 2 mtr head height.

Camper total length closed – 2780mm height closed 1 mtr; width = 1290mm

Camper weights – tare 180kg; gross 260kg

Towbar weight – loaded to rated gross 260kg = 8 to 10kg down load